## Atlas Copco Portable Air compressors



## **XAS 750 JD7 T3**

This generation of the XAS 750 is more environment friendly, more fuel efficient and neatly packaged for serviceability.

Packaged in the new Size II low pressure (single axle, sound suppressed) enclosure, the XAS 750 JD7 is smaller and lighter than competitive packages, and has more key features and benefits. Confirming our commitment to performance, reliability and efficiency.





## Designed to your individual needs

The XAS 750 JD7 is designed with innovative features to make your job easier. For example, all replacement parts are within easy reach so routine maintenance takes less time.

Atlas Copco listened to the sales force, and more importantly we listened to you. We understood your requirements and designed a reliable, high performance air compressor with a long lifetime, low operating costs, and high resale value.

- Guaranteed 750 CFM
- Roadlights standard
- Electronic control module
- Performance and diagnostics at your fingertips





Danger: Compressed air should never be supplied as breathing air unless air is properly purified for breathing. Atlas Copco assumes no responsibility or liability related to the purchaser's/user's breathing air system.

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes

Technical	XAS 750 JD7 T3	
	Imperial	Metric
Normal effective working pressure	100 psi	7 bar
Maximum unloading working pressur	e 125 psi	8.6 bar
Actual free air delivery	750 cfm	345 1/s
Cooling system	Air / Oil	
Oil capacity	33 quarts	31.21
Engine John Deere		
Model number	6068HF285	
Cooling system	Liquid	
Number of cylinders	6	
Capacity of oil sump	36 quarts	341
Capacity of fuel tank	70 gal	2651
Speed - maximum loaded	2000	
Speed - unloaded	1300	
Horsepower	200	
Unit dimentions		
Trailer mounted (LxWxH)	192 x 79 x 83 in	4877 x 2007 x 2108 mm
Support mounted (LxWxH)	132 x 67 x 83 in	3353 x 1702 x 2108 mm
Weight		
Trailer mounted - Wet	7760 lbs	3520 kg
Support mounted - Wet	6790 lbs	3080 kg







